

OMNIGUARD BRUSH

APPLY WITH
paintbrush



or roller

Brush or roll applied temporary protection film for inside use on non-porous surfaces, on construction sites as well as for industrial purposes.



PHASE 1: apply OMNIGUARD BRUSH



PHASE 2: remove film

PRODUCT DESCRIPTION

OMNIGUARD BRUSH is a water based, ready-to-use liquid based on specialty polymer dispersions. This liquid is applied with a paintbrush or (long-haired)roller and dries to a peelable protection film. OMNIGUARD BRUSH protection film can stay on the protected surface up to 12 months. The protection film is easily removed and does not leave any residue. Suitable for inside use.

Possible applications:

- Sanitary: temporary protection during the construction phase of shower trays and bathtubs.
- Industry: protection of (components of) machinery.

ADVANTAGES

- » Cost saving: complete, long term and effective protection;
- » Time saving: simple application with a paintbrush or(long-haired) roller;
- » Water based, solvent free.

APPLICATION

Prior to starting the application:

- » Trial on a little visible area with a paintbrush; remove after 3 days and evaluate;
- » Stir OMNIGUARD BRUSH (do not add solvents or water).

Application:

- » Requirements: T: > 5°C ; dry surface;
- » Apply with paintbrush or (long haired)roller;
- » Total minimum advised consumption: 0,5 kg/m² (~500 micron). If this layer thickness is not reached in one pass, apply in two layers, second layer after the first layer has dried. Wet film gauge to verify thickness can be obtained from the manufacturer or distributor;
- » Depending on temperature, humidity, ventilation and applied thickness, drying time is 4 to 48 hours;
- » Allow sufficient ventilation in case of high humidity level inside the building;
- » Cleaning material: immediately after use with water;
- » Remove OMNIGUARD BRUSH protection film when the protection film is no longer needed.

TEHNICAL DATA

- » View: blue paste; blue protection film after drying;
- » Total advised minimum consumption: 0,5 kg/m² (~500 micron);
- » Density : +/- 1 kg / L;
- » Weather resistant: after 4 to 48 hours (depending conditions);
- » Storage: 5 – 20 °C; store out of direct sunlight;
- » Conservation: 12 months from date of production in unopened and original packaging.

OMNIGUARD BRUSH


product developed and manufactured by www.hevadex.be, Belgium

APPLY WITH
paintbrush



or roller

PRODUCT CERTIFICATIONS

TEST INSTITUTE	TEST	STANDARD	VALUE
SHR	UV- and weather resistance	EN ISO 16474-3:2013	400h
	System evaluation: concrete and window protection	VERITAS	Pass

PACKAGING

- » 2 kg pails ; pallet : 105 x 2 kg
- » 7,2 kg pails ; pallet : 64 x 7,2 kg



SAFETY

Consult the safety data sheet prior to application. Requested to wear eye protection, mouth mask, gloves and safety wear.

EXTRA

SC Silva Termosystems SRL cannot be held liable for damages on surfaces protected with OMNIGUARD Brush.

Date of this edition: 01/07/2019

Our general conditions of sale apply. This document does not have a contractual value. This technical data sheet replaces and annuls the previous edition. The information given in this sheet has the purpose to inform and advice you. At every moment, this sheet can be adapted because of technical evolution. All information is given in good faith and without any warranty. The application, use and processing of these products are beyond our control and therefore the entire responsibility of the user/client/appliator. The user of the product must test the product's suitability and apply for the intended purpose. Established liability if any for any reason is always limited to the value of the goods supplied by SC Silva Termosystems SRL. The products and systems are manufactured under total quality management. HEVADEX bvba reserves the right to change the properties of its products. Users must always refer to the most recent issue of the local Product Data Sheet, copies of which will be supplied on request.